

OD067C Outdoor Series P6.67

960mm x 960mm

Outdoor LED Cabinet

Specifications

Parameter	Value	
Physical Parameter	Pixel Configuration	SMD2727
	Pixel Pitch (mm)	6.667
	Pixel matrix per panel	144x144
	Pixel density (pixels/sq.m.)	22500
	Cabinet Dimensions (WxHxT) (mm)	960x960x133
	Module Dimensions (WxH) (mm)	320x320
	Panel material	steel
	Cabinet weight (kg/panel)	53
Electronic Parameter	Module weight (kg/panel)	1.25
	Color Grayscale (Bit)	14bit
	Gray Scale per Color (level)	16384
	Refresh Rate (Hz)	960--1920
Optical Parameter	Driving Type	1/6
	Brightness (nit)	5500
	Optimal Horizontal Viewing Angle (°)	160
Electrical Parameter	Optimal Vertical Viewing Angle (°)	130/150
	AC Input Voltage (V)	AC: 100V~240V
	AC Input Frequency (Hz)	50/60
	AC Input Power Maximum Value(W/pcs)	573
	AC Input Power Typical Value (W/ pcs)	191
Circumstance Parameter	Storage Temperature (°C)	-40 -60
	Working Temperature (°C)	-30 -50
	IP rating (Front/Rear)	IP65/IP54
	Storage Humidity (RH)	10%-90%non-condensing
	Working Humidity (RH)	10%-90%non-condensing
Installation	Lifetime Typical Value (hrs)	100000
	Cabinet installation	fix



Main Features

- P6.67 LED Display
- Outdoor Applications
- 960x960mm cabinet
- Back Service
- Lower cost
- Steel Cabinet

Mechanical

