



MediaSign Enterprise PCTV-1100 Digital Signage Controller / Player

Unlike most Digital Signage Software requiring a software license, operating system license, and hardware, MediaSign Enterprise offers a robust embedded Digital Signage Player with a zero-software install capability. Managing your player simply requires a network connected device with a modern browser and the MediaSign Enterprise Server. This topology tremendously simplifies the complexity of managing a Digital Signage installation and delivers it in a robust X86 based embedded platform.

Why no software?

Because Media2Stream embeds the signage software directly into the hardware, clients don't have to deal with the messy details of managing, maintaining and learning new (and often difficult to use) software. MediaSign Enterprise offers a pre-configured hardware platform with as minimal a number of failure points as possible, allowing you to run your advertising contents 24x7 worry free. Simply purchase the server to manage the MediaSign Enterprise PCTV-1100. Server licenses are available for 20, 50 100 and >300 client licenses.

Flexible Functionality

The PCTV-1100 features capabilities to play back industry standard contents such as:

- H264 Video (1080p)
- JPG Images
- Adobe Flash 11.x
- HTML 5 (Local HTML pages)
- Crawling Marquee
- Live Streams (RTP RTSP)
- Live URLs (Hosted HTML pages)
- Template based layout (Design your own screen layouts easily with multiple content elements)

From simple images or videos all the way to complex systems with RSS/SOAP/JSON/XML real time feeds. Clients can create complex HTML based content feeds that can be displayed by the PCTV-1100

Optional Audience Detection module
(Gender/Age/Duration) available

Manage Your Contents

- Supports Blocked Time Playlist Support

- Supports Daily Programmes (24 hour time frame)
- Content uploads with Expiration
- LiveView (See what your sign is doing in real time)
- Web based management
- Easy to use



Main Features

- Intel® Celeron Processor J1900
- Integrated Intel® Gen7 Intel® Graphics DX 11, OGL3.2
- 2G Dual Channel DDR3 1333MHz, 2 x SO-DIMM, up to 8GB system memory
- 16G MSATA SSD
- 2xUSB
- 12V DC power supply
- LAN
- HDMI and VGA
- Small footprint player